

INVERTER PRO 2000 C5

EAN 3499231003039



PRODUCT ADVANTAGES

Ergonomic, light and compact equipment

Very Silent

12 V output

Quality current

Low consumption

INVERTER TECHNOLOGY This new, very high performance technology guarantees the stability of the voltage and frequency of your genset to within $\pm 1\%$ of the nominal value. Such high precision makes it possible to produce high-quality current and supply the most demanding equipment.

12V OUTPUT Supplies equipment operating off 12V and in particular for recharging batteries.

Connection cables are included.

Range

PRESTIGE

Top of the range equipment that is efficient and with low noise emissions, for a wide range of standard requirements.

Fuel Petrol

Nominal voltage (V) | Number of Phase 230 | Single phase

Max power (kW) 1,8 kW

75% Autonomy (h) 4,7

Sound power level guaranteed LwA dB(A) 89

Dimensions L x W x H (cm) | Weight (kg) 49 x 36,5 x 44,5 | 21

INVERTER PRO 2000 C5 - GENERATING SET - PRESTIGE - 8 février 2026

portable.rehlko.com

SDMO Industries - 270 rue de Kerervern - CS 40047 - 29801 Brest cedex 9 – France

This document is not contractual - The SDMO company reserves the right to modify any of the characteristics stated in this document without notice, in a constant effort to improve the quality of its products. *ISO 8528.



SDMO Industries
accredited testing laboratory ISO 17025
n°1-2171
scope available on www.cofrac.fr





GENERAL SPECIFICATIONS

Range	PRESTIGE
Frequency (Hz)	50 Hz
Max power (kW)	1,8
Nominal voltage (V)	230
Number of Phase	Single phase
Assigned current (A)	7
Fuel	Petrol
Tank (L)	4,2
75% cons. (l/h)	0,9
75% Autonomy (h)	4,7
Sound power level guaranteed LwA dB(A)	89
Acoustic pressure level @1m in dB(A)	75
Acoustic pressure level @7m in dB(A)	60



ENGINE SPECIFICATIONS

Engine brand	YAMAHA
Engine ref.	MZ80_C5
Start	Starter
Oil shutdown	Oui
Displacement (cm3)	79
Oil system capacity including filters (l)	0,4



ALTERNATOR SPECIFICATION

Technology	Inverter
AVR Regulation	No
Indication of protection	IP 23
Insulation class	H



PLUGS AND PANEL DESCRIPTIVE

1 socket 230V 10/16A - circuit breaker + 1 socket 12V 8A - circuit breaker+ indicator



DIMENSIONS AND WEIGHT

Length (cm)	49
Width (cm)	36,5
Height (cm)	44,5
Dry Weight (kg)	21



PACKAGING

Packaging type	Box
Length (cm)	55,5
Width (cm)	36,5
Height (cm)	49,5
Weight (kg)	22
Pallet type	
Number of box by pallet	6
Pallet height (cm)	53
weight of the packaged Pallet (kg)	150

ACCESSORIES SUPPLIED



Spark plug spanner
User and maintenance manual

Additional equipment

**R05M**

R05M - Manual transfert switch for connecting a single-phase generator to a house

**3499231001790**

RYS2 - Maintenance kit INVERTER PRO 2000 including oil, spark plug and air filter

**RPM**

RPM - Plug kit for all models: 2 x 16A /230V sockets, 1 x CEE17 16A/230V socket, 1 x 32A/230V socket, 1 x 16A/400V socket

**RPQ**

RPQ - 1m earth spike, supplied with 2m 10mm2 mains cable

**RKD1**

RKD1 - Kit of 2 removable differential adaptors for domestic sockets 16A

**3499231000922**

RCC - Coupling cable for connecting 2 generators for INVERTER PRO 2000